## HDMI AMPLIFIERS UH4-4K 1x4 UHD HDMI Splitter



1 in 4 out HDMI<sup>TM</sup> Distribution Amplifier that distributes one ultra high definition source to multiple displays.



## **KEY FEATURES**

- Supports video resolutions up to 4Kx2K @60Hz, 8-bit, 4Kx2K @30Hz, 10-bit, 1080p @60Hz, 12-bit
- 3D ready
- HDMI and HDCP Compliant
- Supports conversion of HDMI signaling to DVI signaling
- Wide frequency range: 25MHz 340MHz
- Cascadable for very large display wall systems
- Heavy duty metal housing. Commercial duty rated
- Integrated EDID in non-volatile memory and DDC support for the HDMI ports using 256-byte SRAM
- Consumer Electronics Control (CEC) interfaces with HDMI-compliant CEC I/O
- Supports Standard Audio, DSD Audio & HD (HBR) Audio
- Locking power connector
- LED Indicators: Input, Output, HDCP, Power
- Integrated Cable retention bracket (CE labs® patented)

## — SPECIFICATIONS

HDMI Input Connector (A-Type Female):	1
HDMI Output Connector (A-Type Female):	4
Video Bandwidth:	10.2 Gbps
Max. Resolution:	4Kx2K @ 60Hz, 8-bit / 4Kx2K @ 30Hz, 10-bit
Cable Distance: (Device to Monitor)	30 ft (Max)
Signal Type:	HDMI V1.4 Compliant/Supports HDMI 2.0
Power Adapter (Min):	DC 12V 1.25A
Housing:	Metal
Weight:	1.5 lbs.
Dimensions:	6.7" L x 6.7" W x 1" H